



DEXRON®-VI ATF AUTOMATIC TRANSMISSION FLUID

Introduction

Petro-Canada DEXRON®-VI is an exceptional automatic transmission fluid approved by General Motors for use in vehicles with automatic transmissions. This unique fluid is specially formulated to provide **twice the service life of a DEXRON®-III (H) ATF and offers enhanced performance for both new and older transmissions.** It is designed to protect your transmission through improved oxidation resistance, friction durability, shear stability and wear protection to help meet warranty protection requirements in late model vehicles. Designed to provide responsive shift feel throughout the life of the oil, Petro-Canada DEXRON®-VI ATF consistently protects your car/truck transmission longer than all previous DEXRON® type fluids.

Petro-Canada DEXRON®-VI ATF was developed in conjunction with General Motors fluid design criteria for all 2006 and beyond model year vehicles with automatic transmissions. It is formulated with Petro-Canada's 99.9% pure PURITY™ Base Oils manufactured using the patented HT Purity Process and an enhanced additive system. Petro-Canada offers you an automatic transmission fluid that is the same high performance fluid as used at the factory for initial fill. In addition, Petro-Canada was granted the first DEXRON®-VI ATF license number from General Motors (J-60001).



Features and Benefits

- **Extended fluid life**
 - Extends life of the transmission
 - Potential to extend drain intervals
- **Enhanced Product Performance for newer and older transmissions**
 - Outstanding resistance against sludge & deposit formation
 - Improved oxidation and thermal stability versus DEXRON®-III (H) ATF
 - Superior anti-wear protection
 - Outstanding low temperature fluidity
 - Enhanced foam control which maintains responsive shifts and reduces wear on bearings, bushing and gears
- **More consistent shifting performance**
 - Optimized frictional properties
 - Prevents clutch shudder in modulated torque converters
 - Extended fluid and clutch durability
 - Smooth gear shifting during low temperature operation
 - Clutch plates and bands last longer
- **Improved Fuel Economy versus DEXRON®-III (H) ATF**
 - Improved torque transfer versus DEXRON®-III (H) ATF
 - More consistent viscosity profile which maintains a consistent torque performance
 - Lower viscosity versus DEXRON®-III (H)
 - Improved shear stability

What is the HT difference?

Petro-Canada starts with the patented HT purity process to produce water-white, 99.9% pure base oils. The result is a range of lubricants, specialty fluids and greases that deliver maximum performance for our customers.



Applications

Petro-Canada DEXRON®-VI ATF is recommended for all 2006 and beyond GM vehicles with Hydramatic automatic transmissions. It is fully back serviceable for DEXRON®-III (H), III(G) and II(E) applications. Meets GM specification, GMN10060.

MB-Approval 236.41

Petro-Canada DEXRON®-VI ATF is approved for use in Mercedes-Benz vehicles requiring a fluid meeting MB 236.41.

Always consult your vehicle owner's manual for specific recommendations.

Typical Product Characteristics

| PROPERTY | TEST METHOD | DEXRON®-VI ATF |
|----------------------|-------------|----------------|
| Density, kg/l @ 15°C | D4052 | 0.846 |
| Colour | - | Red |
| Flash Point, °C / °F | D92 | 206 / 403 |
| Viscosity | | |
| cSt @ 40°C | D445 | 29.8 |
| cSt @ 100°C | | 6.0 |
| Viscosity Index | D2270 | 151 |
| Pour Point, °C / °F | D5950 | -54 / -65 |
| Brookfield Viscosity | | |
| cP @ -20°C | D2983 | 1,053 |
| cP @ -30°C | | 3,164 |
| cP @ -40°C | | 12,030 |
| Sulphated Ash, % wt | D874 | 0.02 |
| Total Base No. | D2896 | 2.0 |
| Qualification Number | | J-60001 |
| Product ID Code | | DEX6 |

The values quoted above are typical of normal production. They do not constitute a specification.

DEXRON® is a registered trademark of General Motors LLC

Health and Safety

Petro-Canada DEXRON®-VI ATF has no adverse effect on health provided it is used as directed. To obtain Material Safety Data Sheets (MSDS), contact one of our TechData Info Lines.

TechData Info Lines

If you would like to know more about **Petro-Canada DEXRON®-VI ATF**, or any other product in our complete line of quality lubricants, please contact us at:

Lubricants Head Office
Petro-Canada Lubricants Inc.
2310 Lakeshore Road West
Mississauga, Ontario
Canada L5J 1K2



Canada - West Phone 1-800-661-1199
- East (English) Phone 1-800-268-5850
(French) Phone 1-800-576-1686
Other Areas Phone (416) 730-2408
E-mail lubecsr@suncor.com
Website lubricants.petro-canada.ca

Petro-Canada Europe Lubricants Limited

Wellington House, Starley Way
Birmingham International Park
Solihull, B37 7HB, United Kingdom

Telephone +44 (0) 121 781 7264
 Fax +44 (0) 121 781 7401
 UK Website www.petro-canada.co.uk
 German Website www.petro-canada.de

Petro-Canada America Lubricants

980 North Michigan Avenue
Suite 1400, #1431
Chicago, Illinois
USA 60611

Phone 1-888-284-4572
 Fax 1-708-246-8994
 E-mail email@petro-canadaamerica.com

Petro-Canada Asia Pacific Holding Company Ltd.

Jia Shi Lubricants Trading (Shanghai) Co. Ltd.
1908 World Trade Tower
500 Guangdong Road, Huangpu District
Shanghai, China 200001

Phone +86-21-6362-0066
 Fax +86-21-6362-0536
 E-mail asiapacific@suncor.com
 Website www.petrocanada.cn

